

## Super QSFP CWDM4-Lite 100G Optical Transceiver



### OVERVIEW

Luxshare-TECH 100Gbps S-QSFP CWDM4-Lite Optical transceiver is designed for 100G Ethernet links with long-reach communication. The link distance up to 500m with single-mode fiber. It integrates four data lanes in each direction with each lane operating at 25.78125 Gbps.

This transceiver also can be used for high density 40G Ethernet applications. They are compliant to IEEE802.3 Clause 140 for 100GBASE-DR and QSFP MSA. The electrical interface is mated with the 38-pin standard QSFP connector. The optical interface uses a duplex LC optical connector. This transceiver utilizes CWDM 1310nm DFB and PIN detect to provide the reliable long life, good performance and quality.

### FEATURES & BENEFITS

- ◆ Hot Pluggable QSFP form factor
- ◆ 4xCWDM DFB Laser/PIN Photo Detector
- ◆ Supports 25.78125Gbps per channel
- ◆ Maximum power consumption 3.5W
- ◆ Up to 500m transmission with SMF
- ◆ Operating Case Temperature: 0°C to +70°C
- ◆ Duplex LC receptacles

### PRODUCT APPLICATIONS

Ethernet for 100GBASE-FR4  
InfiniBand EDR, FDR, & QDR

# Super QSFP CWDM4-Lite 100G Optical Transceiver

## TECHNICAL INFORMATION

### MATERIAL

Nickel plated zinc die cast shells & latching  
Mechanism parts  
Thermoplastic cable pull tab  
Optical plastic lens  
Optical Mux/Demux

### ELECTRICAL PERFORMANCE

Power Supply Voltage: 3.3V (3.14 to 3.46V)  
Data rate per lane: 25.78125Gbps  
Power Consumption: 3.5W(MAX)  
Transmitter Type: DFB  
Receiver Type: PIN

### SPECIFICATIONS

Compliant to 100Gbps CWDM4 MSA  
SFF-8636: Management Interface  
SFF-8661: Pluggable Module  
SFF-8679: General Electrical  
GR-468: Reliability Qualification  
IEEE 802.3bm: Physical Layer Specifications and Management Parameters  
ROHS-6: Environment Safety  
ES-12-00-0036

### Partial PN Table

PN	Package	Description	Reach	Protocol Support	Data Rate	Temp	Power Consumption	Optical Connector	Transceiver	Receiver	WaveLength
PA01QSB01-NC-T	S-QSFP	CWDM4-Lite	500m	Ethernet	100Gbps	0-70°C	3.5W	LC	DFB	PIN	1270-1330nm

### MECHANICAL PERFORMANCE

QSFP Module Insertion: 40N(MAX)  
QSFP Module Extraction: 30N(MAX)  
QSFP Module Retention: 90N(MIN)  
Insertion and removal cycles: 50Cycles

### ENVIRONMENTAL

Storage Temperature Range: -40°C to +85°C  
Operating Temperature Range: 0°C to +70°C  
Relative Humidity: 0 to 85%