

## OCulink Connector



### OVERVIEW

OCuLink is a high speed and high density interconnection solution that can be adopted in PCIe application. Luxshare-TECH provide not only the board connector but the customized corresponding cable for PCIe Gen3 interconnection. The internal and external Small Form Factor PCIe connectors and cables optimized for the client and mobile market that is OCulink focus on. Luxshare's OCulink meets the PCIe 3.0, 8GT/s, enabling optical and copper technology to coexist.

### FEATURES & BENEFITS

- ◆ High density, 4mm height connector to save space
- ◆ 42pin (4i), Vertical and Right Angle types options available
- ◆ Shell with SMT and Through hole options support wide variety of applications
- ◆ Vertical type with enhanced shell design
- ◆ Supports PCIe 3.0 (8GT/s)

### PRODUCT APPLICATIONS

Data center & Networking Equipment  
Servers/Storage Devices  
Switch  
SAS HBA/RAID Controller Card

### INDUSTRY STANDARDS

SFF-8612

## TECHNICAL INFORMATION

### MATERIAL

Contact Base Metal: Copper Alloy  
Contact Area Finish: Gold over Nickel  
Solder Area Finish: Gold over Nickel  
Housing: High temperature thermoplastic(UL 94V-0)  
Shell :Stainless steel  
Shell Finish: Nickel plated

### ELECTRICAL PERFORMANCE

Voltage: 30V AC / contact  
Current: 0.5A / contact

### ENVIRONMENTAL

Operating temperature : -40°C TO +85°C  
Storage temperature : -20°C TO + 85°C

### MECHANICAL PERFORMANCE

Rated Durability Cycles 50

#### Mating force:

w/out latch: 2N~20N

w/Passive latch: 10N~40N

w/Active latch: 8N~40N

#### Unmating force:

w/out latch: 1N~16N

w/Passive latch: 8N~25N

w/Active latch: 8N~25N

### PACKAGING

Tape & Reel

### Partial PN Table

Product Numbers	Product Description
PPC050-4233-TX2-1H	Vertical x4
PPC050-4233-TX3-1H	Vertical x4 Enhanced type
PPC050-4243-TX2-1H	Right Angle x4